

Tool ID: 402  
Tool Location: 106

Equipment Information Sheet  
RC8 spinner (Class II resists)

Manager: Christopher Alpha607-254-4913

Calls to staff phones will be automatically forwarded to their cell phones during accessible hours. At other times leave a message or send them an email.

SAFETY

- All users need to get CNF staff trained prior to tool usage.
- MSDS for all chemical used need to be reviewed
- There are chemical, electrical and mechanical dangers associated with tool operation.

USAGE RESTRICTIONS

- Only CNF Staff can make changes to Slot 9 and Global tool settings

SCHEDULING/SIGN-UP RESTRICTIONS

- None

Minimum Tool Time: 0 minutes

MATERIALS COMPATIBILITY CATEGORY

| Tool Category 5: Class A and B Metals and Compounds |   |
|---|---|
| Allowed   | Not Allowed   |
| Tool category 1/1E, 2, 3, and 4 materials           |   |
| Silicon Based Substrates and Films                  |   |
| III/V compound Semiconductors                       |   |
| Glass Substrates                                    |   |
| PECVD and ALD Films                                 |   |
| Cured organics and baked Photoresist                |   |
| CNF Class A, B, and Refractory metals               |   |
| Exposed Gold, Silver, Copper                        |   |
| Alkali and Alkaline Compounds                       |   |
| Organic/Biology Molecules prepared-w/salt buffers   |   |
| High Vapor Pressure Materials (Mg, Ca, Zn)*         | * Some tool restrictions on high vapor pressure materials may apply |
| Soft organic materials                              |   |

High Vapor Pressure Metals and Compoundsare materials that have a vapor pressure above 1e-6 Torr at 400 C.

Additional Material Restrictions and Exceptions

- Materials Allowed in this Spinner:
  - P-20, KMPR, SU-8 2000, SU-8 3000, Cyclopentanone, Cyclotene, AP 3000
- No Acetone!
- No IPA!
- No Methanol!

Last Updated: 02/17/2023