Equipment Information Sheet

Class 2 Photolithography Spinners

Manager: Giovanni Sartorello 607-254-4853 Calls to staff phones will be automatically forwarded to Backup: James Crawford 607-254-5895 Backup: Tom Pennell 607-254-4309

their cell phones during accessible hours. At other times leave a message or send them an email.

SAFETY

- Face shields must be worn at ALL TIMES.
- Close spinner lid before spinning, for added protection from vacuum or substrate failure.
- No solvents or materials containing solvents outside hoods, except for immediate baking.
- Dispose of waste in appropriate receptacles.

USAGE RESTRICTIONS

- General photolithography training (online and in-person) is required to use this tool.
- Select chuck so that the **substrate is larger than the chuck's vacuum surface**.
- Always use aluminum liner for bowl and wrap lid in aluminum foil.
- Inspect and clean the backside of every substrate after coating and before baking.
- Remove and clean chuck immediately after use.
- Clean around spinner after use with a wipe and minimal acetone.

SCHEDULING/SIGN-UP RESTRICTIONS

Minimum Tool Time: 0 minutes

• None

MATERIALS COMPATIBILITY CATEGORY

Tool Category 5: Class A and B Metals and Compounds

Allowed	Not Allowed
Tool category 1/1E, 2, 3, and 4 materials	
Silicon Based Substrates and Films	
III/V compound Semiconductors	
Glass Substrates	
PECVD and ALD Films	
Cured organics and baked Photoresist	
CNF Class A, B, and Refractory metals	
Exposed Gold, Silver, Copper	
Alkali and Alkaline Compounds	
Organic/Biology Molecules prepared-	
w/salt buffers	
High Vapor Pressure Materials (Mg, Ca,	* Some tool restrictions on high vapor pressure
Zn)*	materials may apply
Soft organic materials	

High Vapor Pressure Metals and Compounds are materials that have a vapor pressure above 1e-6 Torr at 400 C.

Additional Material Restrictions and Exceptions

- Class 2 materials only (SU-8, LOR, PGMI, LOL, KMPR, OmniCoat, Polyimide).
- NO WATER and NO SOLVENTS (acetone, isopropanol, methanol, etc.). Acetone on a wipe may be used to clean chucks and around the spinner.
- No biomaterials.