

Tool ID: 110
Tool Location: 103

Equipment Information Sheet
MOS Metal Anneal 4 - C2

Manager: Phil Infante
Backup: Aaron Windsor

607-254-4926
607-254-4831

Calls to staff phones will be automatically forwarded to their cell phones during accessible hours. At other times leave a message or send them an email.

SAFETY

- The furnaces are run at elevated temperatures of 400-1200°C and use flammable, toxic, and corrosive gases.

USAGE RESTRICTIONS

- No changing of gas flows or process parameters without staff approval
- Max process temperature of 1100 C

SCHEDULING/SIGN-UP RESTRICTIONS

- Reservation blocks greater than 8 hrs must be cleared by a MOS staff person prior to reserving the time

Minimum Tool Time: 90 minutes

MATERIALS COMPATIBILITY CATEGORY

Tool Category 2: Silicon Based Substrates and Select Refractory Metals	
Allowed	Not Allowed
Tool category 1/1E materials	No Glass Substrates
Silicon Based Materials only	No CNF Class A or Class B metals and oxides/compounds of (exposed or buried) (ie Magnesium, Zinc, Barium, Calcium)
Si, SiC, SiO ₂ substrates	
All Furnace grown or deposited films	
PECVD Films	No Gold, Silver or Copper (Exposed or buried)
ALD dielectric films	No High Vapor pressure materials
CNF Refractory Metals (ie Al, Ti,Ta,W,Pt,Mo,Cr,Ni)	No III/V Compound Semiconductors
Nitrides and Oxides of above metals	No Organic/Biology Molecules prepared-with or without Salt buffers
Cured organics and baked Photoresist	

High Vapor Pressure Metals and Compoundsare materials that have a vapor pressure above 1e-6 Torr at 400 C.

Additional Material Restrictions and Exceptions

Last Updated: 03/20/2019